

Materials; — Aluminium, Stainless Steel, Copper, Corten, Mild Steel, Zinc, Perforated.

Allloy specification ((Aluminium) std); - 1000, 3000, 5000

Material gauges (std); - Aluminium 1mm, 1.5mm, 2mm, 3mm. Steel 0.7mm, S/S 0.7mm, Copper 0.7mm, Zinc 0.7mm)

Paint Finishes (std); - Powder coat, Polyester, PVF2, ARS, Granit, Prisma, Promethean®(Imaged) *, Anodised, Corten.




Panel dimensions (std); - **Width** = 100mm up to 650 mm (For flat unstiffened panel depending on substrate, gauge and required aesthetic.) 100 - 300 = 1mm / 100 - 550 = 2mm / 100 - 650 = 3mm. (Based on MCRMA recommendations for Aluminium)

Length = 100mm up to 4metres


Panel thickness (std); - 25mm, 35mm and 42mm. Custom sizes available on request


Warranty period; - Up to 40 years (subject to paint system and environmental conditions)

Available with self cleaning shiplap 45° joint - Yes



(Artisan Plank) (ART-PLA 25mm) (Slim plank)
for materials 1mm –2mm thick
shadow gap 5 -30mm
Option, 130° Shiplap self cleaning joint







(Artisan Plank) (ART-PLA 42mm) (Maxi plank) for materials 1mm to 3mm thick

Shadow gap 5 -30mm (2mm or 3mm)

Option, 130° Shiplap self cleaning joint





(Artisan Plank) (ART-PLA 35mm)(Structural plank) for materials 1mm to 3mm +

Shadow gap 10 -30mm (2mm or 3mm +)

Option, 130° Shiplap self cleaning joint

